

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-21-144

Relating to Certification of New Heavy-Duty Motor Vehicle Engines

CUMMINS ENGINE COMPANY, INC.

Pursuant to the authority vested in the Air Resources Board by Sections 43100, 43102 and 43103 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following Cummins Engine Company, Inc. 1996 model diesel engines are certified for use in motor vehicles with a manufacturer's gross vehicle weight rating (GVWR) over 14,000 pounds:

Fuel Type: Diesel

<u>Engine Family</u>	<u>Liters (Cubic Inches)</u>	<u>Exhaust Emission Control Systems and Special Features</u>
TCE505D6DAAW (413F)	8.3 (505)	Oxidation Catalytic Converter Turbocharger Charge Air Cooler

Engine models and codes are listed on attachments.

The certification exhaust emission standards for this engine family in grams per brake horsepower-hour are:

<u>Total Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Particulates</u>
1.3	15.5	5.0	0.10

The certification exhaust emission values for this engine family in grams per brake horsepower-hour are:


<u>Engine Family</u>	<u>Total Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Particulates</u>
TCE505D6DAAW (413F)	0.2	0.9	4.5	0.06

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachments.

Executed at El Monte, California this 27th day of November 1995.

A handwritten signature in cursive script, appearing to read "John Koralek for".

R. B. Summerfield
Assistant Division Chief
Mobile Source Division

1996 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
HEAVY-DUTY DIESEL-STANDARD ENGINESManufacturer Cummins Engine Company, Inc. Engine Family (413F)TCE505D6DAAWDisplacement: / 8.3 Liters / 505 Cubic InchesMaximum Rated Power: 264 HP @ 2100 RPMEngine Configuration: I-6Ignition: Compression XCompression with Glow Plug Spark Fuel Type(s): Dedicated XFlex-Fuel Dual-Fuel Diesel XM100 M85 CNG LNG LPG Other (specify) Diesel Cert Fuel: 13 CCR 2282 40 CFR 86.1313-90 40 CFR 86.1313-94 XPrimary Intended Service Class: LHD MHD XHHD Urban Bus Exhaust ECS (include MFI, TC, CAC): OC (TC, CAC)

(use abbreviations per SAE J1930 SEP91)

Engine Model (Eng Code)	Rated HP @ RPM	Fuel Rate @ Rated HP mm3 / stroke (lbs/hr)	Fuel Pump & Injector Part No.	ECM/PCM Part No.	EGR Valve Part No.	PTOX / Catalytic Converter Part No.
C8.3-275 (1566)	264 @ 2100	136 (96.0)	FP:3922446 FP:3927923 IN:3922913 IN:3926117 IN:3926120	N/A	N/A	3926265 3929434
C8.3-275 (1566)	260 @ 2200	132 (98.3)	FP:3922427 FP:3927924 IN:3922913 IN:3926117 IN:3926120	N/A	N/A	3926265 3929434
C8.3-250 (1566)	240 @ 2200	120 (89.3)	FP:3922449 IN:3922913 IN:3926117 IN:3926120	N/A	N/A	3926265 3929434

Date Issued: Revisions: